

## White FDA Abrasion Resistant Natural Sheetting

Product Code: RC0305

### Product Description

Our White FDA Abrasion Resistant Natural Sheetting is a high wearing, strong rubber sheetting that has been approved by the FDA for food and drink applications. It has a long life and good overall performance in all applications where high wear and tear protection is a desired property.



Available In -



Full Rolls

Cut to strip

Bespoke  
Gaskets

### Technical Specification

Properties	Test Method	Values
Product	-	FDA Abrasion Resistant Sheetting
Compound	-	NR
Hardness (Shore A)	ASTM D2240	38° ± 5°
Density	ASTM D297	0.98 g/cm <sup>2</sup>
Tensile Strength	ASTM D412	240 kg/cm <sup>2</sup>
Elongation at Break	ASTM D412	810%
Tear Resistance	ASTM D624	40 kg/cm
Abrasion Resistance	ASTM D5963	80 mm <sup>3</sup>
Compression Set (22h, 70°C)	ASTM D395	15%
Working Temperature Range	-	-30°C to + 70°C



The information contained on this product information sheet is to be used as guidance. The advice is given in good faith and does not constitute any guarantee or recommendation for suitability. The Rubber Company cannot be held liable for any damage caused by incorrect installation. We hereby reserve the right to change the technical information herewith without notification or prior agreement.

### Standard Sizes

Properties	Weight [kg/m <sup>2</sup> ]
1mm x 1400mm x 20m	0.98
1.5mm x 1400mm x 20m	1.47
2mm x 1400mm x 20m	1.96
3mm x 1400mm x 10m	2.94
4mm x 1400mm x 20m	3.92
5mm x 1400mm x 10m	4.90
6mm x 1400mm x 10m	5.88
8mm x 1400mm x 10m	7.84
10mm x 1400mm x 10m	9.80



The information contained on this product information sheet is to be used as guidance. The advice is given in good faith and does not constitute any guarantee or recommendation for suitability. The Rubber Company cannot be held liable for any damage caused by incorrect installation. We hereby reserve the right to change the technical information herewith without notification or prior agreement.