

Neoprene Sponge Cord Material Datasheet

Product Code: CRD0201

Product Description

Here at The Rubber Company we can supply high quality neoprene sponge cord in a variety of diameters and lengths to suit any application. These cords are suitable for use in a number of applications in automotive, interior as well as exterior environments. Neoprene cord provides good resistance against UV and ozone deterioration.



Technical Specification

Properties	Values
Compound	Cellular Neoprene (CR)
Colour	Black
Hardness (Shore 00)	45°
Cellular Structure	Closed
Water Absorption	<5%
Linear Shrinkage After (22hrs @ 70°C)	<5%
Compression Set (22hrs @ 23°C)	<25%
Paint Staining (NFT 46-031)	Non-staining
Corrosive Effect on Copper and Silver (NF ISO 6505)	Non-corrosive
Resistance to fuel B ASTM (Change in weight after 7 days @ 23°C)	<150%
Fire Resistance (FMVSS 302)	Conform
Operating Temperature Range	-30°C to +100°C



ISO
9001 : 2015
REGISTERED

The information contained on this product information sheet is to be used as guidance. The advice is given in good faith and does not constitute any guarantee or recommendation for suitability. The Rubber Company cannot be held liable for any damage caused by incorrect installation. We hereby reserve the right to change the technical information herewith without notification or prior agreement.