

High Temp Water Suction Hose - 10 Bar

Product Code: RC07-D-110

Product Description

Crafted using the mandrel technique, this hot water suction and delivery hose is versatile, suitable not only for handling acid and basic solutions but also for applications in steam and heat pumps.

Technical Specification

Inner Diameter	Wall Thickness	Outside Diameter	Working Pressure	Nominal Burst Pressure	Weight	Vacuum	Bending Radius
mm	mm	mm	bar	bar	kg/m	bar	mm
19	5	29	10	55	0.58	0.8	115
25	5	35	10	45	0.72	0.8	150
32	5	42	10	37	0.89	0.8	190
38	5.5	49	10	32	1.16	0.8	230
40	6	52	10	30	1.30	0.8	240
51	6	63	10	30	1.62	0.8	300
63	6	75	10	30	2.10	0.8	380
76	7	90	10	30	2.73	0.8	450
102	8.5	119	10	30	4.56	0.8	600
127	10	147	10	30	6.20	0.8	760

The information contained on this product information sheet is to be used as guidance. The advice is given in good faith and does not constitute any guarantee or recommendation for suitability. The Rubber Company cannot be held liable for any damage caused by incorrect installation. We hereby reserve the right to change the technical information herewith without notification or prior agreement.