

## Metal Reinforced Silicone Edge Trims Datasheet EN45545-2

Product Code: RC01103-MR

### Technical Specification

Property	Unit	Value 60°	Value 70°	Test Method
Specific Gravity	g/cm <sup>3</sup>	1.14	1.18	ISO 1138-1 A
Hardness	Shore A	60	70	DIN 53 505
Tensile Strength	N/mm <sup>2</sup>	11	11	DIN 53 504 S1
Elongation at Break	%	490	520	DIN 53 504 S1
Tear Strength	KN/m	21	26	ASTM D 624 B
Rebound Resistance	%	59	51	DIN 53 512
Compression Set (22h/175°C)	%	25	35	ISO 815-B
Ignition Temperature approx.	850°C			
Operating Temperature	-60°C to +280°C			

### Flammability (Acc. EN45545-2)

Property	Unit
Classification	R22/R23, HL 1-3
Smoke Density (Ds max)	36.9
Oxygen Index (LOI)	79.9
Toxicity (CIT NLP)	0.0



ISO  
9001 : 2015  
REGISTERED

The information contained on this product information sheet is to be used as guidance. The advice is given in good faith and does not constitute any guarantee or recommendation for suitability. The Rubber Company cannot be held liable for any damage caused by incorrect installation. We hereby reserve the right to change the technical information herewith without notification or prior agreement.